

MULCH & GROW

PREMIUM CELLULOSE MULCH

A low-cost DOT Type I product for use on shallow slopes – dead level to 4:1. Premium paper fibers and super absorbing polymer (SAP 1500) retain water and prevent surface erosion due to raindrop impact.

Shorter premium paper fibers result in faster blending and also help stop settling in tanks and clumping in nozzles, causing easier application.

- 97% fibers 3% super absorbent polymer
- A true hydrophilic engineered fiber
- Precision Fiberized fibers
- No paper mache effect
- Excellent water retention through the use of premium products and fiberization process
- Better end results with accelerated germination

PHYSICAL PROPERTIES:

| | |
|------------------------|---------------|
| Moisture Content | 12% + - 3 |
| Organic Content | 98.4% + - 2 |
| Ash Content | 1.6% + - 2 |
| pH Range | 5.5 + - 1 |
| Water Holding Capacity | 1500% Minimum |

APPLICATIONS:

Carolina Fiber products may be used in a wide range of applications, such as erosion control, golf courses, highway work, and residential.



**50 lb. Bag covers up to
~1,000 sq. ft.
Product #11015**

APPLICATION RATES:

Hydro Seeding

| | |
|---------------|------------------------|
| 1500 lbs/acre | Moderate to 3.1 Slope |
| 2000 lbs/acre | 3.1 to 2.1 Slope |
| 2500 lbs/acre | Greater than 2.1 Slope |

Hydro Mulching/Binding

750 lbs/acre